

HXHLQ-H4A33

Four frequency combiner

Technical Data Sheet

Serial	Parameters	CDMA-RX	CDMA-TX	GSM-RX	GSM-TX
1	Frequency Range	825~835MHz	870~880MHz	889~915MHz	934~960MHz
2	Insertion Loss	≤1.8dB	≤1.8dB	≤1.8dB	≤1.8dB
3	VSWR	≤1.3:1	≤1.3:1	≤1.3:1	≤1.3:1
4	Rejection	≥60dB@ 870~880MHz	≥60dB@ 825~835MHz	≥60dB@ 825~835MHz	≥60dB@ 825~835MHz
		≥60dB@ 889~915MHz	≥60dB@ 889~915MHz	≥60dB@ 870~880MHz	≥60dB@ 870~880MHz
		≥60dB@ 934~960MHz	≥60dB@ 934~960MHz	≥60dB@ 934~960MHz	≥60dB@ 889~915MHz
5	Surface Finish	Black Paint			
6	Connectors	ANT:SMA-Female ; Other:SMA-Female			
7	Port Sign	Port1:ANT ; Port2:825-835MHz ; Port3:870-880MHz ; Port4:889-915MHz ; Port5:934-960MHz			
8	Configuration	As Below (Size Unit: mm)			

