

HXHLQ-H2A35

Cavity Diplexer

Technical Data Sheet

S/N	Item	Parameters	
		RX	TX
1	Center Frequency(F0)	2150MHz	2350MHz
2	Pass Band Frequency	2100 ~ 2200MHz	2300 ~ 2400MHz
3	Pass Band Insertion Loss	≤1.0dB	≤1.0dB
4	Pass Band VSWR	≤1.3:1	≤1.3:1
5	Stop Band Rejection	≥60dB @ 2300 ~ 2400MHz	≥60dB @ 2100 ~ 2200MHz
6	Impedance	50 Ohms	
7	Power	20W Max.	
8	Connectors	SMA-Female	
9	Surface Finish	Painted Black	
10	Port Sign	Port 1: ANT ; Port 2: RX ; Port 3: TX	
11	Temperature Range	-30℃ ~ +70℃	
12	Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Resonant column: H59 Copper alloy Connectors: H59 Copper, Plated ternary alloy Other screw: Stainless Steel
13	Dimensions	192*56*26mm	
14	Net weight	TBD	

Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.7mm)

