

- **Model:** HXLBQ-DZA241
- **Product Name:** Cavity Band Rejection Filter
- **Frequency:** 758~803MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Stop Band Frequency	758 ~ 803MHz	
● Stop Band Attenuation	≥60dB	
● Pass Band Frequency	DC ~ 735MHz , 849 ~ 2300MHz	
● Pass Band Insertion Loss	≤1.5dB	
● Pass Band VSWR	≤1.5:1 @ DC ~ 735MHz , 849 ~ 2000MHz ≤1.7:1 @ 2000 ~ 2300MHz	
● Impedance	50 Ohms	
● Power	10W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-20°C ~ +60°C	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	265*80*28mm	
● Net weight	1.0 KG	
●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)		

