

- **Model:** HXLBQ-DTA182
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 25.5~26.5GHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters	
● Center Frequency(F0)	26GHz	
● Pass Band Bandwidth	1.0GHz (25.5 ~ 26.5GHz)	
● Pass Band Insertion Loss	≤1.5dB	
● Pass Band VSWR	≤1.3:1	
● Stop Band Rejection	≥40dB @ DC ~ 24GHz	≥40dB @ 28 ~ 35GHz
● Impedance	50 Ohms	
● Power Handling	5W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-20°C ~ +60°C	
● Material	Housing: H62 Copper alloy Cover: H62 Copper alloy Tuning screw: H62 Copper alloy	Connectors: H59 Copper, Plated ternary alloy Other screw: Stainless Steel
● Dimensions	38*16*7.5mm	
● Net weight	TBD	

●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

