

- **Model:** HXLBQ-DTA192
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 2085~2115MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters	
● Center Frequency(F0)	2100MHz	
● Pass Band Frequency	2085 ~ 2115MHz	
● Pass Band Insertion Loss	≤3.0dB	
● Pass Band Ripple	≤0.7dB	
● Pass Band VSWR	≤1.3:1	
● Stop Band Attenuation	≥60dB @ DC ~ 2040MHz	≥60dB @ 2160 ~ 6000MHz
● Impedance	50 Ohms	
● Power Handling	5W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Connectors: H59 Copper, Plated ternary alloy Cover: LY12 Aluminum alloy Other screw: Stainless Steel Tuning screw: H62 Copper alloy	
● Dimensions	113*25*20mm	
● Net weight	TBD	

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

