

- **Model:** HXLBQ-DTA150
- **Product Name:** Interdigital Band Pass Filter
- **Frequency:** 950~1500MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters	
● Center Frequency(F0)	1225MHz	
● Pass Band Frequency	950 ~ 1500MHz	
● Pass Band Insertion Loss	≤1.5dB	
● Pass Band VSWR	≤1.6:1	
● Stop Band Rejection	≥30dB @ Fc±70MHz (DC ~ 880MHz、1570 ~ 2000MHz)	
● Impedance	50 Ohms	
● Power	10W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Connectors: H59 Copper, Plated ternary alloy Cover: 6061 Aluminum alloy Other screw: Stainless Steel Tuning screw: H62 Copper alloy	
● Dimensions	93*65*11mm	
● Net weight	TBD	

●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

