

- **Model:** HXLBQ-DTA167
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 880~915MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters	
● Center Frequency(F0)	897.5MHz	
● Pass Band Frequency	880 ~ 915MHz	
● Pass Band Insertion Loss	≤2.0dB	
● Pass Band VSWR	≤1.3:1	
● Stop Band Rejection	≥50dB @ DC ~ 860MHz	≥40dB @ 925 ~ 935MHz
	≥40dB @ 860 ~ 870MHz	≥50dB @ 935 ~ 2700MHz
● Impedance	50 Ohms	
● Power Handling	20W Max.	
● Connectors	N-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy	Connectors: H59 Copper, Plated ternary alloy
	Cover: LY12 Aluminum alloy	Other screw: Stainless Steel
	Tuning screw: H62 Copper alloy	
● Dimensions	120*62*41mm	
● Net weight	TBD	

●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

