

- **Model:** HXLBQ-DTA188
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 5725~5850MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters	
● Center Frequency(F0)	5787.5MHz	
● Pass Band Frequency	5725 ~ 5850MHz	
● Pass Band Insertion Loss	≤0.6dB	
● Pass Band VSWR	≤1.3:1	
● Stop Band Attenuation	≥40dB @ Fc±200MHz (DC ~ 5525MHz , 6050 ~ 9000MHz)	
● Impedance	50 Ohms	
● Power	100W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Resonant column: H59 Copper alloy Cover: LY12 Aluminum alloy Connectors: H59 Copper, Plated ternary alloy Tuning screw: H62 Copper alloy Other screw: Stainless Steel	
● Dimensions	100*20*20mm	
● Net weight	TBD	

●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

