

- **Model:** HXLBQ-DTA208
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 1420~1440MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	1430MHz	
● Pass Band Frequency	1420 ~ 1440MHz	
● Pass Band Insertion Loss	≤1.0dB	
● Pass Band Ripple	≤0.4dB	
● Pass Band VSWR	≤1.22:1	
● Stop Band Attenuation	≥80dB @ DC ~ 1000MHz	≥50dB @ 1460 ~ 1860MHz
	≥55dB @ 1000 ~ 1400MHz	≥80dB @ 1860 ~ 6500MHz
● Impedance	50 Ohms	
● Power Handling	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-20°C ~ +60°C	
● Material	Housing: 6061 Aluminum alloy	Resonant column: H59 Copper alloy
	Cover: LY12 Aluminum alloy	Connectors: Stainless Steel
	Tuning screw: H62 Copper alloy	Other screw: Stainless Steel
● Dimensions	107*73*26mm	
● Net weight	0.31 KG	
●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)		

