

- **Model:** HXLBQ-DTA211
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 991~1009MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters	
● Center Frequency(F0)	1000MHz	
● Pass Band Frequency	991 ~ 1009MHz	
● Pass Band Insertion Loss	≤2.0dB	
● Pass Band VSWR	≤1.3:1	
● Stop Band Rejection	≥40dB @ Fc±10MHz (DC ~ 981MHz , 1019 ~ 2600MHz)	
● Impedance	50 Ohms	
● Power Handling	20W Max	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Resonant column: H59 Copper alloy Connectors: H59 Copper, Plated ternary alloy Other screw: Stainless Steel
● Dimensions	120*62*41mm	
● Net weight	TBD	

●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

