

- **Model:** HXLBQ-DTA229
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 2496~2690MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters	
● Center Frequency(F0)	2593MHz	
● Pass Band Frequency	2496 ~ 2690MHz	
● Pass Band Insertion Loss	≤1.0dB	
● Pass Band Return Loss	≤18dB	
● Stop Band Rejection	≥65dB @ DC ~ 2300MHz	≥40dB @ 2886 ~ 4000MHz
● Impedance	50 Ohms	
● Power	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Resonant column: H59 Copper alloy Cover: LY12 Aluminum alloy Connectors: H59 Copper, Plated ternary alloy Tuning screw: H62 Copper alloy Other screw: Stainless Steel	
● Dimensions	92*92*26mm	
● Net weight	TBD	

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

