

- **Model:** HXLBQ-DTA349
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 2400~2485MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters	
● Center Frequency(F0)	2442.5MHz	
● Pass Band Frequency	2400 ~ 2485MHz	
● Pass Band Insertion Loss	≤2.0dB	
● Pass Band Ripple	≤1.5dB	
● Pass Band VSWR	≤1.3:1	
● Stop Band Rejection	≥40dB @ DC ~ 2393MHz	≥40dB @ 2492 ~ 5000MHz
● Impedance	50 Ohms	
● Power Handling	120W Max.	
● Connectors	N-Male / N-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Resonant column: H59 Copper alloy Connectors: H59 Copper, Plated ternary alloy Other screw: Stainless Steel
● Dimensions	121*91*26mm	
● Net weight	TBD	

●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

