

- **Model:** HXLBQ-DZA233
- **Product Name:** Cavity Band Rejection Filter
- **Frequency:** 1850~1915MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Stop Band Frequency	1850 ~ 1915MHz	
● Stop Band Attenuation	≥60dB	
● Pass Band Frequency	DC ~ 1810MHz , 1970 ~ 5100MHz	
● Pass Band Insertion Loss	≤1.5dB (at the corner: 2.0dB Max.)	
● Pass Band VSWR	≤1.5:1	
● Impedance	50 Ohms	
● Power Handling	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-10°C ~ +50°C	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	209*44*22mm	
● Net weight	TBD	
●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)		

