

- **Model: HXLBQ-DTA1087X**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 1075~1105MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	1090MHz	
● Pass Band Frequency	1075 ~ 1105MHz **	
● Pass Band Insertion Loss	≤1.5dB	
● Pass Band Ripple	≤0.9dB	
● Pass Band Return Loss	≥20dB	
● Stop Band Rejection	≥50dB @ DC ~ 1060MHz	≥50dB @ 1120 ~ 4000MHz
● Impedance	50 Ohms	
● Power Handling	20W Max.	
● Connectors	N-Female / SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-20°C ~ +60°C	
● Material	Housing: 6061 Aluminum alloy Resonant column: H59 Copper alloy Cover: LY12 Aluminum alloy Connectors: H59 Copper, Plated ternary alloy Tuning screw: H62 Copper alloy Other screw: Stainless Steel	
● Dimensions	120*62*31mm	
● Net weight	TBD	

** The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.4mm)

