

- **Model:** HXLBQ-DTA1109
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 3995~4005MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	4000MHz	
● Pass Band Frequency	3995 ~ 4005MHz **	
● Pass Band Insertion Loss	≤1.5dB	
● Pass Band Ripple	≤0.3dB	
● Pass Band Return Loss	≥23dB	
● Stop Band Rejection	≥80dB @ DC ~ 3865MHz	≥50dB @ 4080 ~ 4135MHz
	≥50dB @ 3865 ~ 3920MHz	≥80dB @ 4135 ~ 12000MHz
● Impedance	50 Ohms	
● Power Handling	10W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy	Connectors: Stainless Steel
	Cover: LY12 Aluminum alloy	Other screw: Stainless Steel
	Tuning screw: H62 Copper alloy	
● Dimensions	110*21*17mm	
● Net weight	0.08 KG	

** The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

