

- **Product Name: High Pass Filter**
- **Model: HXLBQ-GTA14**
- **Frequency: 2.0~19GHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ Small Size

Technical Data Sheet	
Item	Parameters
● Cut Off Frequency	2.0GHz
● Pass Band Frequency	2.0 ~ 19GHz
● Pass Band Insertion Loss	≤1.4dB @ 2.0 ~ 2.1GHz    ≤0.9dB @ 2.1 ~ 19GHz
● Pass Band VSWR	≤1.5:1
● Stop Band Attenuation	≥50dB @ DC ~ 1.58GHz
● Impedance	50 Ohms
● Power Handling	15W Max.
● Connectors	SMA-Female
● Surface Finish	Guide Oxygen or Painted Black
● Temperature Range	-55°C ~ +85°C
● Net weight	0.025 KG
● <b>Outline Drawing:</b> (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)	
◆ <b>Material</b>	<ul style="list-style-type: none"> <li>● Housing: Aluminum alloy</li> <li>● Screw: Stainless Steel</li> </ul> <ul style="list-style-type: none"> <li>● Connectors: Stainless Steel</li> <li>● Dimensions: 37*18*10mm</li> </ul>

