

- **Product Name: High Pass Filter**
- **Model: HXLBQ-GTA17**
- **Frequency: 2.75~21GHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ Small Size

Technical Data Sheet	
Item	Parameters
● Cut Off Frequency	2.75GHz
● Pass Band Frequency	2.75 ~ 21GHz
● Pass Band Insertion Loss	≤1.5dB @ 2.75 ~ 2.85GHz ≤1.0dB @ 2.85 ~ 21GHz
● Pass Band VSWR	≤1.5:1
● Stop Band Attenuation	≥50dB @ DC ~ 2.2GHz
● Impedance	50 Ohms
● Power Handling	15W Max.
● Connectors	SMA-Female
● Surface Finish	Guide Oxygen or Painted Black
● Temperature Range	-55°C ~ +85°C
● Net weight	0.02 KG

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|---------------------------|-------------------------------|
| ◆ Material | ● Housing: Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Screw: Stainless Steel | ● Dimensions: 33*17*10mm |

