

- **Product Name: High Pass Filter**
- **Model: HXLBQ-GTA71**
- **Frequency: 10~24GHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ Small Size

Technical Data Sheet	
Item	Parameters
● Cut Off Frequency	10GHz
● Pass Band Frequency	10 ~ 24GHz
● Pass Band Insertion Loss	≤2.0dB @ 10 ~ 10.5GHz ≤1.0dB @ 10.5 ~ 24GHz
● Pass Band VSWR	≤1.5:1
● Stop Band Attenuation	≥60dB @ DC ~ 9.17GHz
● Impedance	50 Ohms
● Power Handling	15W Max.
● Connectors	SMA-Female
● Surface Finish	Guide Oxygen or Painted Black
● Temperature Range	-55°C ~ +85°C
● Net weight	0.02 KG

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|---------------------------|-------------------------------|
| ◆ Material | ● Housing: Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Screw: Stainless Steel | ● Dimensions: 28*22*10mm |

