

- **Model: HXLBQ-DZA225X**
- **Product Name: Cavity Band Rejection Filter**
- **Frequency: 643~678MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Stop Band Frequency	643 ~ 678MHz
● Stop Band Attenuation	≥50dB
● Pass Band Frequency	DC ~ 613MHz , 733 ~ 1800MHz
● Pass Band Insertion Loss	≤1.0dB
● Pass Band VSWR	≤1.5:1 @ 330 ~ 613MHz , 733 ~ 1800MHz ≤1.6:1 @ DC ~ 330MHz
● Impedance	50 Ohms
● Power Handling	10W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	0°C ~ +40°C
● Net weight	TBD

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|-------------------------------|
| ◆ Material | ● Housing: 6061 Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Cover: LY12 Aluminum alloy | ● Working Environment: Indoor |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 265*104*28mm |

