

- **Model: HXLBQ-DZA223X**
- **Product Name: Cavity Band Rejection Filter**
- **Frequency: 578~608MHz**
- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Stop Band Frequency	578 ~ 608MHz
● Stop Band Attenuation	≥45dB
● Pass Band Frequency	DC ~ 548MHz , 658 ~ 1500MHz
● Pass Band Insertion Loss	≤1.0dB
● Pass Band VSWR	≤1.5:1 @ 310 ~ 548MHz , 658 ~ 1500MHz ≤1.7:1 @ DC ~ 310MHz
● Impedance	50 Ohms
● Power Handling	10W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	0°C ~ +50°C
● Net weight	TBD

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|-------------------------------|
| ◆ Material | ● Housing: 6061 Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Cover: LY12 Aluminum alloy | ● Working Environment: Indoor |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 265*115*28mm |

