

- **Model:** HXLBQ-DZA72S
- **Product Name:** Cavity Band Rejection Filter
- **Frequency:** 934~954MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Stop Band Frequency	934 ~ 954MHz
● Stop Band Attenuation	≥50dB
● Pass Band Frequency	DC ~ 914MHz , 974 ~ 2500MHz
● Pass Band Insertion Loss	≤1.5dB
● Pass Band VSWR	≤1.5:1
● Impedance	50 Ohms
● Power Handling	10W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	0°C ~ +40°C
● Net weight	0.75 KG

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- |                   |                                  |                               |
|-------------------|----------------------------------|-------------------------------|
| ◆ <b>Material</b> | ● Housing: 6061 Aluminum alloy   | ● Connectors: Stainless Steel |
|                   | ● Cover: LY12 Aluminum alloy     | ● Working Environment: Indoor |
|                   | ● Tuning screw: H62 Copper alloy | ● Dimensions: 221*87*28mm     |

