

- **Model:** HXLBQ-DZA110
- **Product Name:** Cavity Band Rejection Filter
- **Frequency:** 876.2~915MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

**Technical Data Sheet**

Item	Parameters
● Stop Band Frequency	876.2 ~ 915MHz
● Stop Band Attenuation	≥40dB
● Pass Band Frequency	DC ~ 854MHz , 937 ~ 2400MHz
● Pass Band Insertion Loss	≤1.5dB
● Pass Band VSWR	≤1.5:1
● Impedance	50 Ohms
● Power	20W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-20°C ~ +60°C
● Net weight	0.73KG

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- |                   |                              |  |
|-------------------|------------------------------|--|
| ◆ <b>Material</b> | ● Housing: Aluminum alloy    | ● Connectors: H59 Copper, Plated ternary alloy |
|                   | ● Cover: Aluminum alloy      | ● Working Environment: Indoor                  |
|                   | ● Tuning screw: Copper alloy | ● Dimensions: 221*87*28mm                      |

