

- **Model:** HXLBQ-DZA112
- **Product Name:** Cavity Band Rejection Filter
- **Frequency:** 1447.9~1462.9MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Stop Band Frequency	1447.9 ~ 1462.9MHz
● Stop Band Attenuation	≥50dB
● Pass Band Frequency	DC ~ 1417MHz , 1492 ~ 3000MHz
● Pass Band Insertion Loss	≤2.0dB
● Pass Band VSWR	≤1.5:1
● Impedance	50 Ohms
● Power	20W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-20°C ~ +60°C
● Net weight	TBD

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|--|
| ◆ Material | ● Housing: 6061 Aluminum alloy | ● Connectors: H59 Copper, Plated ternary alloy |
| | ● Cover: LY12 Aluminum alloy | ● Working Environment: Indoor |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 173*65*22mm |

