

- **Model:** HXLBQ-DZA99
- **Product Name:** Cavity Band Rejection Filter
- **Frequency:** 824~849MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Stop Band Frequency	824~849MHz
● Stop Band Attenuation	≥40dB
● Pass Band Frequency	DC~795MHz & 878~2000MHz
● Pass Band Insertion Loss	≤2.0dB
● Pass Band VSWR	≤1.5:1
● Impedance	50 ohms
● Power Handling	≤10W
● Connectors	SMA-Female
● Surface Finish	Black Paint
● Temperature Range	0°C~+50°C
● Net Weight	0.83 KG

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|-------------------------------|
| ◆ Material | ● Housing: 6061 Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Cover: LY12 Aluminum alloy | ● Working Environment: Indoor |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 221*92*28mm |

