

- **Model: HXLBQ-DZA132**
- **Product Name: Cavity Band Rejection Filter**
- **Frequency: 4400~5000MHz**
- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Stop Band Frequency	4400 ~ 5000MHz
● Stop Band Attenuation	≥50dB
● Pass Band Frequency	DC ~ 4250MHz , 5150 ~ 10000MHz
● Pass Band Insertion Loss	≤2.5dB
● Pass Band VSWR	≤1.7:1
● Impedance	50 Ohms
● Power Handling	5W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

<p>◆ Material</p> <ul style="list-style-type: none"> ● Housing: 6061 Aluminum alloy ● Cover: LY12 Aluminum alloy ● Tuning screw: H62 Copper alloy 	<ul style="list-style-type: none"> ● Connectors: Stainless Steel ● Working Environment: Indoor ● Dimensions: 141*34*16mm
---	---

