

- **Model:** HXLBQ-DZA170
- **Product Name:** Cavity Band Rejection Filter
- **Frequency:** 1300~1500MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

**Technical Data Sheet**

Item	Parameters
● Stop Band Frequency	1300 ~ 1500MHz
● Stop Band Attenuation	≥40dB
● Pass Band Frequency	DC ~ 1240MHz , 1560 ~ 3900MHz
● Pass Band Insertion Loss	≤1.5dB (Typical: ≤1.0dB)
● Pass Band VSWR	≤1.5:1 @ 550 ~ 1240MHz , 1560 ~ 3900MHz ≤1.8:1 @ DC ~ 550MHz
● Impedance	50 Ohms
● Power Handling	10W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- |                   |                                  |                               |
|-------------------|----------------------------------|-------------------------------|
| ◆ <b>Material</b> | ● Housing: 6061 Aluminum alloy   | ● Connectors: Stainless Steel |
|                   | ● Cover: LY12 Aluminum alloy     | ● Working Environment: Indoor |
|                   | ● Tuning screw: H62 Copper alloy | ● Dimensions: 234*58*28mm     |

