

- **Model:** HXLBQ-DZA216
- **Product Name:** Cavity Band Rejection Filter
- **Frequency:** 2010~2200MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Stop Band Frequency	2010 ~ 2200MHz
● Stop Band Attenuation	≥50dB
● Pass Band Frequency	DC ~ 1953MHz , 2245 ~ 5700MHz
● Pass Band Insertion Loss	≤1.8dB
● Pass Band VSWR	≤1.5:1 @ DC ~ 1953MHz , 2245 ~ 5300MHz ≤1.7:1 @ 5300 ~ 5700MHz
● Impedance	50 Ohms
● Power Handling	10W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|--------------------------------|
| ◆ Material | ● Housing: 6061 Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Cover: LY12 Aluminum alloy | ● Other screw: Stainless Steel |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 209*39*22mm |

