

- **Model:** HXLBQ-DZA228
- **Product Name:** Cavity Band Rejection Filter
- **Frequency:** 3300~3800MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Stop Band Frequency	3300 ~ 3800MHz
● Stop Band Attenuation	≥50dB
● Pass Band Frequency	DC ~ 3100MHz , 4000 ~ 8000MHz
● Pass Band Insertion Loss	≤1.2dB
● Pass Band VSWR	≤1.7:1
● Impedance	50 Ohms
● Power Handling	5W Max.
● Connectors	N-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	0.25 KG

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|--|
| ◆ Material | ● Housing: 6061 Aluminum alloy | ● Connectors: H59 Copper, Plated ternary alloy |
| | ● Cover: LY12 Aluminum alloy | ● Working Environment: Indoor |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 141*43*18mm |

