

- **Model: HXLBQ-DZA234**
- **Product Name: Cavity Band Rejection Filter**
- **Frequency: 2500~2570MHz**
- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Stop Band Frequency	2500 ~ 2570MHz
● Stop Band Attenuation	≥60dB
● Pass Band Frequency	DC ~ 2475MHz , 2595 ~ 6500MHz
● Pass Band Insertion Loss	≤2.0dB (at the corner: 3.0dB Max.)
● Pass Band VSWR	≤1.5:1
● Impedance	50 Ohms
● Power	50W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-20°C ~ +60°C
● Dimensions	209*37*22mm
● Net weight	0.345 KG
● Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)	
◆ Material	<ul style="list-style-type: none"> ● Housing: Aluminum alloy ● Connectors: Stainless Steel ● Cover: Aluminum alloy ● Other screw: Stainless Steel ● Tuning screw: Copper alloy

