

- **Model:** HXLBQ-DZA268
- **Product Name:** Cavity Band Rejection Filter
- **Frequency:** 889~949MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

**Technical Data Sheet**

Item	Parameters
● Stop Band Frequency	889 ~ 949MHz
● Stop Band Attenuation	≥50dB
● Pass Band Frequency	DC ~ 857MHz , 981 ~ 2800MHz
● Pass Band Insertion Loss	≤1.0dB
● Pass Band VSWR	≤1.5:1
● Impedance	50 Ohms
● Power Handling	10W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-10°C ~ +50°C
● Net weight	TBD

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- |                   |                                  |                               |
|-------------------|----------------------------------|-------------------------------|
| ◆ <b>Material</b> | ● Housing: 6061 Aluminum alloy   | ● Connectors: Stainless Steel |
|                   | ● Cover: LY12 Aluminum alloy     | ● Working Environment: Indoor |
|                   | ● Tuning screw: H62 Copper alloy | ● Dimensions: 265*79*28mm     |

